

# 500L JoJo Backwash Tank

An innovative design that allows for pool backwash water to be saved and re-used.

## TANK DIMENSIONS

**01**

**STORAGE**

500 L

**02**

**TANK HEIGHT**

1 080mm

**03**

**DIAMETER**

840mm

**04**

**WEIGHT**

13kg (when empty)

**05**

**LID**

480mm Clip-on-Lid with E-clips



### ADDITIONAL COMPONENTS REQUIRED

- Standard garden hose to move water from tank back to the pool and to the garden.
- A 40mm layflat hose is recommended to transfer water from pool filter back wash to the tank.

## FEATURES & BENEFITS:

### FEATURES INCLUDE:


- Made from transparent UV resistant polymer so that water quality is visible.
- Purpose located tap off points are provided to ensure only clean water is returned to your pool and dirty water can be used in your garden.
- Lightweight and durable for both mobile and permanent applications.

### THE BACKWASH TANK INCLUDES:

- Inlet - 40mm Female Fitting
- Overflow - 40mm Female Fitting
- Outlet - 40mm Water Fitting complete with:
  - 25mm Ball Valve
  - 40/25 Reducer
  - 25mm Barrel Nipple
  - 20mm Accessory Adaptor
- 2nd Outlet - 20mm Fitting complete with:
  - 20mm Tommy Tap & 20mm Tap Connector

# 500L JoJo Backwash Tank


## INSTALLATION/ASSEMBLY



**01**

Fit Tommy tap (B) to 20mm water fitting (A) on the tank and 20mm tap connector (C) to the tap.


*Note: this tap is used to return clear water to the pool*



**02**


Fit ball valve assembly (B) to 40mm inlet (A) at the bottom of the tank, then fit the accessory adaptor (C) to the ball valve assembly. *Note: the ball valve will be used to return settled pool waste to the garden.*

## APPLICATION



**01**


Place tank in the desired location relative to filter and pool. Ensure that it is placed on a base that is sound, level, smooth, free from any protrusions and at least 100mm wider than the base of the tank.



**02**


**a)** Connect a 40mm layflat hose from your pool backwash line to your overflow/inlet at the top of the tank.

**b)** Backwash your pool and fill the tank with your backwash water. Allow the water to settle.



**03**

Connect a hose to the 20mm tap connector and return the clear water to the pool.



**04**

When this is complete, connect a hose to the accessory adaptor on the ball valve assembly and divert the dirty water into the desired area in your garden.