

Leaf Eater Advanced™ Rain Head

HOW THE LEAF EATER WORKS:

The Leaf Eater prevents debris from entering the Rainwater Harvesting System, improves water quality and reduces tank maintenance. All of which are undesirable elements to have in a water storage system.

The single screen deflects leaves and debris away from the flow of water. This minimises maintenance and enhances catchment efficiency. This Rain Head incorporates a VH Pivot™ outlet that swivels to suit vertical or horizontal downpipes.


The Leaf Eater Advanced™ can also be used as a debris removing device even when rainwater is not being collected.

MAINTENANCE


- The Clean Shield screen is mostly self cleaning.
- If cleaning is required, simply lift the Clean Shield outwards, then hose or brush off.

FEATURES & BENEFITS

- Compact, versatile rainhead for quick and easy installation.
- Patented single screen technology for advanced debris shedding.
- Minimal maintenance required
- Pivot the outlet to suit vertical or horizontal (rear outlet) downpipes.
- High flow rate performance.
- Superior catchment efficiency at low and high flow rates.
- Single screen with mosquito proof stainless steel mesh.
- Reduces tank maintenance
- Improves the quality of rainwater harvested



Horizontal Position




Vertical position



Leaf Eater Advanced™ Rain Head

GUTTER & MID-MOUNT INSTALLATION

1. Gutter: Measure 208mm from the bottom of the existing gutter pop and remove this section of downpipe. Ensure the cut edge is clean and smooth. Mid-Mount: Remove 208mm of downpipe where the Leaf Eater Advanced™ is to be situated. Ensure cut edges are clean and smooth (figure 1).
2. Using the quick release tabs remove the Cleanshield™ screen by lifting it up and then out (figure 2).
3. Insert the Leaf Eater Advanced™ by sliding it up over the cut section and then down into position. The Leaf Eater Advanced™ outlet should be slid firmly onto the bottom down pipe until it can be pushed no further (figure 3).
4. Screw the Leaf Eater Advanced™ into position through the screw slots provided. Ensure appropriate screws and anchors (if required) are used (figure 5).
5. Insert the Cleanshield™ into the Leaf Eater Advanced™. Ensure the Cleanshield™ screen is sitting firmly in place and check installation that the installation is secure (figure 6).



HORIZONTAL (REAR OUTLET INSTALLATION)

1. Using the quick release tabs remove the Cleanshield™ screen by lifting it up and out (figure 2).
2. Swivel the outlet to the horizontal position - some force may be required.
3. Position the Leaf Eater Advanced™ next to existing pipework, mark and cut top and bottom cut lines (as per figure 4). Ensure the cut edge is clean and smooth.
4. Insert the Leaf Eater Advanced™ by sliding the rear outlet into the horizontal pipe. The back fixing pipe must sit behind the top section of downpipe (figure 3).
5. Screw the Leaf Eater Advanced™ into position through the screw slots provided. Ensure appropriate screws and anchors (if required) are used (figure 5).
6. Insert the Cleanshield™ screen into the Leaf Eater Advanced™ Screen. Ensure the Cleanshield™ screen is sitting firmly in place and check installation is secure (figure 6).

